

PROFESSIONAL CATERING EQUIPMENT



	P10		P14		P19		P23
	P10		P15		P19		P23
	P11		P15		P20		P24
	P11		P16		P20		P24
	P12		P16		P21		P25
	P12		P17		P21		P25
	P13		P17		P22		P26
	P13		P18		P22		P27
	P14		P18		P22		P27

	P28		P32		P37		P41
	P28		P33		P37		P42
	P29		P33		P38		P42
	P29		P34		P38		P43
	P30		P34		P39		P43
	P30		P35		P39		P44
	P31		P35		P40		P44
	P31		P36		P40		P45
	P32		P36		P41		P45

	P46		P50		P55		P59
	P46		P51		P55		P60
	P47		P51		P56		P60
	P47		P52		P56		P61
	P48		P52		P57		P61
	P48		P53		P57		P62
	P49		P53		P58		P62
	P49		P54		P58		P63
	P50		P54		P59		P63



DF-8L-V

Electric Fryer

- 3250W powerful heater with 8 Liters oil capacity
- Stainless steel structure with drain tap
- Thermostat 50-190°C
- 230°C Hi-limiter ensures safety operation
- Stainless steel tank with oil level
- Micro-switch for safety of operators
- Heater would stop automatically once heater is lifted up
- Stainless steel night cover with Bakelite handle, cool to touch
- Stainless steel board to collect fried crumbs from food and protect heater
- Power and heating indicators
- Nickel coating basket
- Heavy duty anti slippery foot
- Heating elements can be lifted for easy cleaning
- V shape cold zone to prevent food debris scorching

Model	Capacity	Power	Product (WxDxH)	NW
DF-8L-V	8 L	3250 W / 220~240V	330 x 480 x 345 mm 13 x 19 x 13.6 inch	10.5 kg 23 lbs
DF-8L-2V	2 x 8 L	2 x 3250 W / 220~240V	600 x 480 x 345 mm 24 x 19 x 14 inch	20 kg 44 lbs



DF-11L



DF-11L-2

Electric Fryer

- Compact design, available in 8 models
- Stainless steel structure
- Thermostat 50-190°C
- Stainless steel tank with oil level
- Micro-switch for safety of operators
- Heater would stop automatically once heater is lifted up
- Stainless steel night cover with Bakelite handle, cool to touch
- Wire mesh net to collect fried crumbs from food and protect heater
- Power and heating indicators
- Nickel coating basket
- Heavy duty anti slippery foot
- Electric box can be removed for easy cleaning
- 230°C hi-limiter ensures safety operation

Model	Capacity	Power	Product (WxDxH)	NW
DF-4L	4 L	2000 W / 220~240 V	217 x 400 x 320 mm 9 x 16 x 13 inch	6 kg 13 lbs
DF-6L	6 L	2500 W / 220~240 V	265 x 430 x 295 mm 10 x 17 x 12 inch	7 kg 15 lbs
DF-8L	8 L	3250 W / 220~240 V	265 x 430 x 345 mm 10 x 17 x 14 inch	8 kg 18 lbs
DF-11L	11 L	3500 W / 220~240 V	325 x 460 x 345 mm 13 x 18 x 14 inch	9 kg 20 lbs
DF-4L-2	2 x 4 L	2 x 2000 W / 220~240 V	435 x 400 x 320 mm 17 x 16 x 13 inch	10 kg 22 lbs
DF-6L-2	2 x 6 L	2 x 2500 W / 220~240 V	550 x 430 x 295 mm 22 x 17 x 12 inch	11 kg 24 lbs
DF-8L-2	2 x 8 L	2 x 3250 W / 220~240 V	550 x 430 x 345 mm 22 x 17 x 14 inch	14 kg 31 lbs
DF-11L-2	2 x 11 L	2 x 3500 W / 220~240 V	670 x 460 x 345 mm 26 x 18 x 14 inch	17 kg 37 lbs



EF-DF

Electric Fryer

- 3000W powerful heater with 11 Liters oil capacity
- Stainless steel structure with drain tap
- Thermostat 30-200°C
- Water-proof on/off switch
- 230°C hi-limiter ensures safety operation
- Stainless steel tank with oil level
- Micro-switch for safety of operators
- Heater would stop automatically once heater is lifted up
- Stainless steel night cover with Bakelite handle, cool to touch
- Wiring grid to collect fried crumbs from food and protect heater
- Power and heating indicators
- Nickel coating wire mesh trays
- Heavy duty anti slippery foot
- Heating elements can be lifted for easy cleaning
- Two functions lid: cover during night, draining tray while frying

Model	Capacity	Power	Product (WxDxH)	NW
EF-DF	11 L	3000 W / 220~240 V	545 x 460 x 355 mm 55 x 18 x 14 inch	17 kg 37 lbs



DF-8T

Electric Fryer

- 3250W powerful heater with 8Litres oil capacity
- Stainless steel structure with drain tap
- Thermostat 50-190°C
- 230°C hi-limiter ensures safety operation
- Stainless steel tank with oil level
- Micro-switch for safety of operators
- Heater would stop automatically once heater is lifted up
- Stainless steel night cover with Bakelite handle, cool to touch
- Wire mesh net to collect fried crumbs from food and protect heater
- Power and heating indicators
- Nickel coating basket
- Heavy duty anti slippery foot
- Electric box can be removed for easy cleaning
- Bottom cold zone to prevent food debris scorching



DF-8T-2

Model	Capacity	Power	Product (WxDxH)	NW
DF-8T	8 L	3250W / 220~240 V	290 x 550 x 410 mm 11 x 22 x 16 inch	10 kg 22 lbs
DF-8T-2	2 x 8 L	2 x 3250W / 220~240 V	580 x 550 x 410mm 23 x 22 x 16 inch	17.5kg 39 lbs



EF-71



EF-72

Gas Fryer

- Cast aluminum burner
- Stainless steel structure with surrounded insulation
- 5.5 Liters capacity tank
- Stainless steel tank with oil level
- Stainless steel night cover with Bakelite handle, cool to touch
- Nickel coating basket
- Heavy duty anti slippery foot
- Observation hole in the front for visual of the burner fire
- Gas valve with sparking electrode
- Tank can be taken out for easy cleaning

Model	Capacity	Power	Product (WxDxH)	NW
EF-71	5.5 L	18000Btu / 5.27kW	290 x 520 x 445 mm 11 x 20 x 18 inch	12 kg 26 lbs
EF-72	2 x 5.5 L	36000Btu / 10.54 kW	580 x 520 x 445 mm 23 x 20 x 18 inch	22 kg 48 lbs



EF-71T



EF-72T

Gas Fryer

- Round tube heat exchanger immersed in oil for best efficiency
- Stainless steel structure
- 8 Liters capacity per tank
- Stainless steel tank with oil level
- Thermostat range 160~220°C
- Steel drain cock
- Nickel coating basket
- Heavy duty anti slippery foot
- Observation hole in the front for visual of the burner fire
- Gas valve with sparking electrode
- Compact design, available in single tank and double tanks

Model	Capacity	Power	Product (WxDxH)	NW
EF-71T	8 L	10239 Btu / 3 kW	315 x 610 x 532 mm 12 x 24 x 20.9 inch	14 kg 31 lbs
EF-72T	2 x 8 L	20478 Btu / 6 kW	610 x 610 x 532 mm 24 x 24 x 21 inch	26 kg 57 lbs



DF-B

Electric Fryer

- Stainless steel structure
- Stainless steel heating elements
- 10 L capacity tank
- Bakelite handle
- Drain extension tube
- Night cover included

Model	Capacity	Power	Product (WxDxH)	NW	GW
DF-B	10 L	8.1 kW / 380 V	360 x 473 x 320 mm 14 x 19 x 13 inch	17 kg 37 lbs	19 kg 42 lbs
DF-BA	10 L	6 kW / 380 V	360 x 473 x 320 mm 14 x 19 x 13 inch	17 kg 37 lbs	19 kg 42 lbs



OV-20

Electric fryer with cabinet

- Stainless steel frying pot, 40 pounds capacity
- Stainless steel front and galvanized sides
- On/off power switch
- 12kw flat heating elements for best heat transfer
- Deep cold zone with forward sloping bottom
- 1 inch drainage valve
- Oil draining extension
- Cool to touch Bakelite door handle
- Two baskets

Model	Capacity	Power	Voltage	Product (WxDxH)	NW
OV-20	28 L	12 kW	380 V / 3N	400 x 690 x 1120 mm 16 x 27 x 44 inch	56 kg 123 lbs



DF-28L



DF-28L-2

Electric Fryer

- 18KW powerful heater with 28 Litres oil capacity each
- Robust structure with drain tap
- Thermostat 50-190°C
- 230°C hi-limiter ensures safety operation
- Stainless steel tank with oil level
- Stainless steel night cover with Bakelite handle, cool to touch
- Wire mesh net to collect fried crumbs from food and protect heater
- Heater lifting mechanism to make cleaning easy and comfortable
- Power and heating indicators
- Nickel coating basket
- Heavy duty steel foot
- Timing relay with buzzer for reminder
- Bottom cold zone to prevent food debris scorching

Model	Capacity	Power	Product (WxDxH)	NW
DF-28L	28 L	18kW / 380 V	400 x 800 x 1100 mm 16 x 32 x 43 inch	56 kg 123 lbs
DF-28L-2	2 x 28 L	2 x 18 kW / 380 V	800 x 800 x 1100 mm 32 x 42 x 43 inch	101 kg 222 lbs



DF-28LD

Electric Fryer

- 18KW powerful heater with 28Litres oil capacity each
- PCB control with programming function
- Preset melting function at 82°C
- Robust structure with drain tap
- Temperature range is 50-190°C
- Precise timing setting
- 230°C hi-limit ensures safety operation
- Stainless steel tank with oil level
- Stainless steel night cover with Bakelite handle, cool to touch
- Wire mesh net to collect fried crumbs from food and protect heater
- Heater lifting mechanism to make cleaning easy and comfortable
- Power and heating indicators
- Nickel coating basket
- Heavy duty steel foot
- Bottom cold zone to prevent food debris scorching

Model	Capacity	Power	Product (WxDxH)	NW
DF-28LD	28 L	18 kW / 380V	400 x 800 x 1100 mm 16 x 32 x 43 inch	56 kg 123 lbs
DF-28LD-2	2 x 28 L	2 x 18 kW / 380V	800 x 800 x 1100 mm 32 x 425 x 43 inch	101 kg 222 lbs



DF-10L-2

Electric Fryer

- 6KW powerful heater with 10Litres oil capacity each
- Split tank with separate control system
- Robust structure with drain tap
- Thermostat 50-190°C
- 230°C hi-limiter ensures safety operation
- Stainless steel tank with oil level
- Stainless steel night cover with Bakelite handle, cool to touch
- Wire mesh net to collect fried crumbs from food and protect heater
- Heater lifting mechanism to make cleaning easy and comfortable
- Power and heating indicators
- Nickel coating basket
- Heavy duty steel foot
- Bottom cold zone to prevent food debris scorching

Model	Capacity	Power	Product (WxDxH)	NW
DF-10L-2	2 x 10 L	6 + 6 kW / 380 V	400 x 800 x 1100 mm 16 x 32 x 43 inch	56 kg 123 lbs



VX15

Electrical Food Warmer

- Stainless steel structure
- Stainless steel sheathed heating elements on top
- Heating elements for even heat distribution compared with lamps
- Mirror polished radiant plate against heater to improve efficiency
- Easy access from 3 sides for food
- Can be used to keep French fries or any food warm
- Separate on/off switches for lamp and heater
- Pan runner inside the cabinet
- Basket hanger rod
- Perforated liners for drainage of Fries grease
- Stainless steel adjustable legs
- Stainless steel handle

Model	Lamp	Power	Product (WxDxH)	NW
VX15	40 W	940 W / 230 V	400 x 759 x 1250 mm 16 x 30 x 49 inch	40 kg 88 lbs



DNB-6

Noodle Boiler

- Stainless steel structure
- Stainless steel heating elements
- Auto lifting mechanism
- Split tank
- Timing function to cook food
- PCB control panel, easy to operate
- Steel foot

Model	Power	Product (WxDxH)	NW	GW
DNB-6	18 kW / 380V	570 x 770 x 880 mm 22 x 30 x 35 inch	75 kg 165 lbs	100 kg 220 lbs



WJRM16

Gas Noodle Boiler

- 24L capacity tank, SUS316
- Flame failure safety control valve
- Two powerful burners
- Electrode sparkler
- Foam drainage in the front
- Stainless steel basket with Bakelite handle
- Stainless steel adjustable leg

Model	Power	Gas Types	Product (WxDxH)	NW	GW
WJRM16	9.6 kW	NG / LP	403 x 773 x 1070 mm 16 x 30 x 42 inch	60 kg 132 lbs	73 kg 161 lbs



YSD-1AE

Convection Oven

- 62L capacity cavity 460×375×360 mm
- Stainless steel structure
- Thermostat 50-300°C
- 360°C hi-limit ensures safety operation
- Stainless steel cavity or ceramic coating cavity
- 120 minutes timer with bell
- Steel handle fixed by Bakelite base
- Dual round heaters plus two high speed motors
- Stainless steel baffle to generate heat more evenly
- Timing and heating indicators
- Chamber light for better view of cooking process
- Nickel coating pan support
- Four aluminum baking trays 325×450mm
- Optional wiring grid 325×450mm
- Good insulation at 5 sides
- Rounded corners in cavity for easy cleaning
- Door latch opens at 90° for easy access to the cavity
- Level distance is 75mm
- Double toughened visual glass for better view and to keep cool to touch
- Steaming function is available for YSD-2A

Model	Chamber	Steaming	Power	Product (WxDxH)	NW
YSD-1AE	Ceramic coating	Nil	2.67 kW / 220 ~ 240 V	595 x 530 x 570 mm 23 x 21 x 22 inch	38 kg 84 lbs
YSD-1A	Stainless steel	Nil	2.67 kW / 220 ~ 240 V	595 x 530 x 570 mm 23 x 21 x 22 inch	38 kg 84 lbs
YSD-2A	Stainless steel	Yes	2.67 kW / 220 ~ 240V	595 x 530 x 570 mm 23 x 21 x 22 inch	38 kg 84 lbs



YSD-1AE-TD

Convection Oven

- 62L capacity cavity 460×375×360 mm
- Stainless steel structure
- Thermostat 50-300°C
- 360°C hi-limiter ensures safety operation
- Stainless steel cavity or ceramic coating cavity
- 120 minutes timer with bell
- Steel handle fixed by Bakelite base
- Dual round heaters plus two high speed motors
- Stainless steel baffle to generate heat more evenly
- Timing and heating indicators
- Chamber light for better view of cooking process
- Nickel coating pan support
- Four wiring grid 325×450mm
- Good insulation at 5 sides
- Rounded corners in cavity for easy cleaning
- Door latch opens at 90° for easy access to the cavity
- Level distance is 75mm
- Double toughened visual glass for better view and to keep cool to touch
- Hourly cooking capacity is 60pcs of potatoes
- Oval-shaped top holding space

Model	Chamber	Power	Product (WxDxH)	NW
YSD-1AE-TD	Ceramic coating	2.87 kW / 220 ~ 240 V	652 x 640 x 895 mm 26 x 25 x 35 inch	70 kg 154 lbs
YSD-1A-TD	Stainless steel	2.87 kW / 220 ~ 240 V	652 x 640 x 895 mm 26 x 25 x 35 inch	70 kg 154 lbs



YSD-4A-B

Convection Oven

- 62L capacity cavity 460×375×360 mm
- Stainless steel structure
- Thermostat 50-300°C
- 360°C hi-limiter ensures safety operation
- Stainless steel cavity
- 120 minutes timer with bell
- Steel handle fixed by Bakelite base
- Dual round heaters plus two high speed motors
- Stainless steel baffle to generate heat more evenly
- Timing and heating indicators
- Chamber light for better view of cooking process
- Nickel coating pan support
- Four aluminum baking trays 325×450mm
- Optional wiring grid 325×450mm
- Good insulation at 5 sides
- Rounded corners in cavity for easy cleaning
- Door latch opens at 90° for easy access to the cavity
- Level distance is 75mm
- Double toughened visual glass for better view and to keep cool to touch
- Manual steaming function is available for YSD-4A
- Grilling is perfect for finish of the cooked products
- 9- Position EGO selective switch EGO
- Top inner(1.7kW), Top out(0.7kW), Bottom(1.7kW), Back(1.26kWx2)

Model	Chamber	Steaming	Power	Product (WxDxH)	NW
YSD-4A-B	Stainless steel	Yes	2.67 kW /220 ~ 240 V	595 x 530 x 570 mm 23 x 21 x 22 inch	41 kg 90 lbs
YSD-4A-BM	Stainless steel	Yes	3.52 kW /220 ~ 240 V	595 x 530 x 570 mm 23 x 21 x 22 inch	41 kg 90 lbs



YSD-4AD

Convection Oven

- 62L capacity cavity 460×375×360 mm
- Stainless steel structure
- PCB control with programming function for 5 menus
- Easy conversion from program to manual(5-stages cooking)
- Temperature range is 5-260°C
- Cook & Hold, holding temperature@65°C
- 360°C hi-limiter ensures safety operation
- Stainless steel cavity or ceramic coating cavity
- Precise timing function to seconds ,up to 99 minutes 59 seconds
- Chamber light for better view of cooking process
- Steel handle fixed by Bakelite base
- Dual round heaters plus two high speed motors
- Stainless steel baffle to generate heat more evenly
- Trip switch to stop working when door is opened
- Nickel coating pan support
- Four aluminum baking trays 325×450mm
- Optional wiring grid 325×450mm
- Good insulation at 5 sides
- Rounded corners in cavity for easy cleaning
- Door latch opens at 90° for easy access to the cavity
- Level distance is 75mm
- Double toughened visual glass for better view and to keep cool to touch
- Steaming function is available for YSD-4AD

Model	Chamber	Steaming	Power	Product (WxDxH)	NW
YSD-3AD	Stainless steel	Nil	2.67 kW / 2.15 kW / 220 ~ 240 V	595 x 530 x 570 mm 23 x 21 x 22 inch	39 kg 86 lbs
YSD-4AD	Stainless steel	Yes	2.67 kW / 2.15 kW / 220 ~ 240 V	595 x 530 x 570 mm 23 x 21 x 22 inch	41 kg 90 lbs



YSD-1AD

Convection Oven

- 62L capacity cavity 460×375×360 mm
- Stainless steel structure
- PCB control with programming function for 5 menus
- Easy conversion from program to manual (5-stages cooking)
- Temperature range is 5-260°C
- Cook & Hold, holding temperature@65°C
- 360°C hi-limiter ensures safety operation
- Stainless steel cavity or ceramic coating cavity
- Precise timing function to seconds , up to 99 minutes 59 seconds
- Chamber light for better view of cooking process
- Steel handle fixed by Bakelite base
- Dual round heaters plus two high speed motors
- Stainless steel baffle to generate heat more evenly
- Trip switch to stop working when door is opened
- Nickel coating pan support
- Four aluminum baking trays 325×450mm
- Optional wiring grid 325×450mm
- Good insulation at 5 sides
- Rounded corners in cavity for easy cleaning
- Door latch opens at 90° for easy access to the cavity
- Level distance is 75mm
- Double toughened visual glass for better view and to keep cool to touch
- Steaming function is available for YSD-2AD

Model	Chamber	Steaming	Power	Product (WxDxH)	NW
YSD-1AED	Ceramic coating	Nil	2.67 kW / 220 ~ 240 V	595 x 530 x 570 mm 23 x 21 x 22 inch	38 kg 84 lbs
YSD-1AD	Stainless steel	Nil	2.67 kW / 220 ~ 240 V	595 x 530 x 570 mm 23 x 21 x 22 inch	38 kg 84 lbs
YSD-2AD	Stainless steel	Yes	2.67 kW / 220 ~ 240 V	595 x 530 x 570 mm 23 x 21 x 22 inch	38 kg 84 lbs

Convection Oven



YSD-8AD

- 116L capacity cavity 700×460×360 mm
- Stainless steel structure
- PCB control with programming function for 5 menus
- Easy conversion from program to manual(5-stages cooking)
- Temperature range is 5-260°C
- Cook & Hold, holding temperature@65°C
- 360°C hi-limiter ensures safety operation
- Stainless steel cavity or ceramic coating cavity
- Precise timing function to seconds ,up to 99 minutes 59 seconds
- Chamber light for better view of cooking process
- Steel handle fixed by Bakelite base
- Dual round heaters plus two high speed motors
- Auto-reverse, 90s(clockwise) + 13s(stop) + 90s(anticlockwise)
- Stainless steel baffle to generate heat more evenly
- Trip switch to stop working when door is opened
- Nickel coating pan support
- Four aluminum baking trays 600×400mm
- Optional wiring grid 600×400mm
- Good insulation at 5 sides
- Rounded corners in cavity for easy cleaning
- Door latch opens at 90° for easy access to the cavity
- Level distance is 75mm
- Double toughened visual glass for better view and to keep cool to touch

Model	Chamber	Steaming	Power	Product (WxDxH)	NW
YSD-8AD	Ceramic coating	Yes	6.4 kW / 220 ~ 240 V / 380 V 2N	834 x 672 x 572 mm 33 x 27 x 23 inch	73 kg 161 lbs
YSD-8ADS	Stainless steel	Yes	6.4 kW / 220 ~ 240 V / 380 V 2N	834 x 672 x 572 mm 33 x 27 x 23 inch	73 kg 161 lbs



YSD-4A

Convection Oven

- 62L capacity cavity 460×375×360 mm
- Stainless steel structure
- Thermostat 50-300°C
- 360°C hi-limiter ensures safety operation
- Stainless steel cavity
- 120 minutes timer with bell
- Steel handle fixed by Bakelite base
- Dual round heaters plus two high speed motors
- Stainless steel baffle to generate heat more evenly
- Timing and heating indicators
- Chamber light for better view of cooking process
- Nickel coating pan support
- Four aluminum baking trays 325×450mm
- Optional wiring grid 325×450mm
- Good insulation at 5 sides
- Rounded corners in cavity for easy cleaning
- Door latch opens at 90° for easy access to the cavity
- Level distance is 75mm
- Double toughened visual glass for better view and to keep cool to touch
- Manual steaming function is available for YSD-4A
- Grilling is perfect for finish of the cooked products

Model	Chamber	Steaming	Power	Product (WxDxH)	NW
YSD-3A	Stainless steel	Nil	2.67 kW / 2.15 kW / 220 ~ 240 V	595 x 530 x 570 mm 23 x 21 x 22 inch	39 kg 86 lbs
YSD-4A	Stainless steel	Yes	2.67 kW / 2.15 kW / 220 ~ 240 V	595 x 530 x 570 mm 23 x 21 x 22 inch	41 kg 90 lbs



YSD-1A-BQ

Convection Oven

- 28L capacity cavity 350×290×275 mm
- Stainless steel structure
- Thermostat 50-300°C
- 360°C hi-limiter ensures safety operation
- Stainless steel chamber
- 120 minutes timer with bell
- Steel handle fixed by Bakelite base
- Round heater plus high speed motor to stir heat evenly
- Stainless steel baffle to generate heat more evenly
- Timing and heating indicators
- Chamber light for better view of cooking process
- Nickel coating pan support
- Three wiring grid 325×265mm, GN1/2 size
- Good insulation at 5 sides
- Rounded corners in cavity for easy cleaning
- Door latch opens at 90° for easy access to the cavity
- Level distance is 75mm
- Double toughened visual glass for better view and to keep cool to touch

Model	Chamber	Steaming	Power	Product (WxDxH)	NW
YSD-1A-BQ	Stainless steel	Nil	2.67 kW / 220 ~ 240 V	460 x 556 x 460 mm 18 x 22 x 18 inch	27 kg 59 lbs

Convection Oven



YSD-8A

- 116L capacity cavity 700×460×360 mm
- Stainless steel structure
- Temperature range is 30-300°C
- 120 minutes timer with bell
- 360°C hi-limiter ensures safety operation
- Stainless steel cavity or ceramic coating cavity
- Manual spraying switch for direct steam
- Chamber light for better view of cooking process
- Steel handle fixed by Bakelite base
- Dual round heaters plus two high speed motors
- Stainless steel baffle to generate heat more evenly
- Trip switch to stop working when door is opened
- Nickel coating pan support
- Four aluminum baking trays 600×400mm
- Optional wiring grid 600×400mm
- Good insulation at 5 sides
- Rounded corners in cavity for easy cleaning
- Door latch opens at 90° for easy access to the cavity
- Level distance is 75mm
- Double toughened visual glass for better view and to keep cool to touch
- Steaming function

Model	Chamber	Steaming	Power	Product (WxDxH)	NW
YSD-8A	Ceramic coating	Yes	6.4 kW / 220 ~ 240 V / 380 V 2N	834 x 672 x 572 mm 33 x 27 x 23 inch	73 kg 161 lbs
YSD-8AS	Stainless steel	Yes	6.4 kW / 220 ~ 240 V / 38 0V 2N	834 x 672 x 572 mm 33 x 27 x 23 inch	73 kg 161 lbs

Convection Oven



YSD-8A-3

- 93L capacity cavity 700×460×288 mm
- Stainless steel structure
- Thermostat 50-300°C
- 360°C hi-limit ensures safety operation
- Stainless steel cavity
- 120 minutes timer with bell
- Steel handle fixed by Bakelite base
- Dual round heaters plus two high speed motors
- Stainless steel baffle to generate heat more evenly
- Timing and heating indicators
- Chamber light for better view of cooking process
- Nickel coating pan support
- Three aluminum baking trays 400×600mm
- Optional wiring grid 400×600mm
- Good insulation at 5 sides
- Rounded corners in cavity for easy cleaning
- Door latch opens at 90° for easy access to the cavity
- Level distance is 75mm
- Double toughened visual glass for better view and to keep cool to touch

Model	Chamber	Steaming	Power	Product (WxDxH)	NW
YSD-8A-3	Stainless steel	Nil	3.5 kW / 220 ~ 240 V	834 x 672 x 500 mm 33 x 27 x 20 inch	70 kg 154 lbs



YSD-6A

Convection Oven

- Stainless steel structure
- Stainless steel heating elements
- Enameled cavity for easy cleaning
- 4 standard GN1/1 rack
- Bakelite handle
- Cook & Hold function
- Water proof switch

Model	Power	Product (WxDxH)	NW	GW
YSD-6A	2.85 kW / 230 V	796 x 670 x 580 mm 31 x 26 x 23 inch	44 kg 97 lbs	52 kg 114 lbs



YSD-6AJ

Convection Oven

- Stainless steel structure
- Stainless steel heating elements
- Enameled cavity for easy cleaning
- 4 standard GN1/1 rack
- Bakelite handle
- Selection switch for top and bottom heaters
- Water proof switch

Model	Power	Product (WxDxH)	NW	GW
YSD-6AJ	4 kW / 230 V	796 x 670 x 580 mm 31 x 26 x 23 inch	44 kg 97 lbs	52 kg 114 lbs



YSD-B

Convection Oven

- Compact 30L capacity cavity 405×255×300 mm
- Stainless steel structure
- Thermostat 50-300°C
- Stainless steel chamber
- 120 minutes timer with bell
- Cool to touch Bakelite handle
- Round heater plus high speed motor to stir heat evenly
- Stainless steel baffle to generate heat more evenly
- Timing and heating indicators
- Visual toughened glass for better view of cooking process
- Stainless steel grid support
- One wiring grid 400×290mm
- Oil collector 419×299mm
- Good insulation at 5 sides
- Rounded corners in cavity for easy cleaning
- Door latch opens at 90° for easy access to the cavity
- Level distance is 75mm

Model	Chamber	Steaming	Power	Product (WxDxH)	NW
YSD-B	Stainless steel	Nil	2.5 kW / 220 ~ 240 V	527 x 450 x 315 mm 21 x 18 x 12 inch	18 kg 40 lbs



YSD-100

Convection Oven

- Robust structure
- Stainless steel heating elements
- Enameled cavity for easy cleaning
- Can fit full sheet size baking tray
- High quality spring steel seal
- Double speeds motor
- Heavy duty fan blade

Model	No. of Tray	Power	Product (WxDxH)	NW	GW
YSD-100	11	12.4 kW / 380 V	967 x 1099 x 1384 mm 38 x 43 x 55 inch	180 kg 396 lbs	218 kg 480 lbs



GR-800

Static Oven

- 80L capacity cavity 500×530×300mm
- Stainless steel structure
- Thermostat 100-320°C
- Stainless steel cavity
- Piezo ignitor
- Standby pilot for main burner
- Flame failure with thermal coupling
- Cool to touch Bakelite handle
- Stainless steel burner to generate heat more evenly
- Stainless steel heavy duty insulated door
- Heavy duty hinge for commercial use
- Nickel coating wiring grid
- Good insulation at 4 sides
- Door latch opens at 90° for easy access to the cavity
- Level distance is 70mm
- 3 levels design

Model	Chamber	Temperature	Power	Product (WxDxH)	NW
GR-800	Stainless steel	100 - 320°C	24000 Btu / 7kW	800 x 900 x 580 mm 32 x 35 x 23 inch	71 kg 156 lbs



YSD-06

Electric Boilerless Combi Steamer

- All stainless steel structure
- Stainless steel heating elements
- Heavy duty stainless steel cavity
- Standard GN1/1 rack High quality silicon seal
- Boilerless to generate steam, free from water scale
- Heavy duty fan blade

Model	No. of Tray	Power	Product (WxDxH)	NW	GW
YSD-06	6	12 kW / 380 V	867 x 918 x 750 mm 34 x 36 x 30 inch	152 kg 334 lbs	182 kg 400 lbs
YSD-10	10	18 kW / 380 V	867 x 918 x 930 mm 34 x 36 x 37 inch	180 kg 396 lbs	218 kg 480 lbs



KC-DU

Slow Cooker

- Stainless steel structure
- Flexible heating foils outside the chamber
- 130°C maximum to cook food slowly
- Probe function to detect core temperature of food
- Timing function to cook food
- PCB control panel, easy to operate
- Rubber foot

Model	Power	Product (WxDxH)	NW	GW
KC-DU	1.25 kW / 220~240 V	495 x 690 x 420 mm 20 x 27 x 17 inch	26 kg 57 lbs	27 kg 59 lbs



PG-MA

Panini Grill

- Cast iron plate with ceramic coating to improve efficiency
- Stainless steel structure
- EGO thermostat, durable and robust
- Temperature range 50-320°C
- Hi-limiter ensures safety operation
- Easy access to Reset pole
- Rotating shaft suspension system
- Stainless steel oil collector
- Bakelite handle, cool to touch
- Steel wire pipe to last longer
- Easy access to back rotating shaft, easy to adjust tightness
- Anti slippery rubber foot
- Rock on/off switch with illuminator
- Different plate type available

Model	Plate type	Cooking size	Power	Product (WxDxH)	NW
PG-SA	Top grooved + bottom grooved	214 x 214 mm 8 x 8 inch	1800 W / 220 ~ 240 V	290 x D05 x 210 mm 11 x 12 x 8 inch	14 kg 31 lbs
PG-SF	Top flat + bottom flat	214 x 214 mm 8 x 8 inch	1800 W / 220 ~ 240 V	290 x 305 x 210 mm 11 x 12 x 8 inch	14 kg 31 lbs
PG-SC	Top grooved + bottom flat	214 x 214 mm 8 x 8 inch	1800 W / 220 ~ 240 V	290 x 305 x 210 mm 11 x 12 x 8 inch	14 kg 31 lbs
PG-MA	Top grooved + bottom grooved	338 x 220 mm 13 x 9 inch	2200 W / 220 ~ 240 V	410 x 305 x 210 mm 16 x 12 x 8 inch	19 kg 42 lbs
PG-MB	Top flat + bottom flat	338 x 220 mm 13 x 9 inch	2200 W / 220 ~ 240 V	410 x 305 x 210 mm 16 x 12 x 8 inch	19 kg 42 lbs
PG-MC	Top grooved + bottom flat	338 x 220 mm 13 x 9 inch	2200 W / 220 ~ 240 V	410 x 305 x 210 mm 16 x 12 x 8 inch	19 kg 42 lbs



PG-815

Panini Grill

- Mild steel plate with hard chrome coating to improve efficiency
- Stainless steel structure
- Top grooved, bottom flat plate
- Temperature range 50-300°C
- Rotating shaft suspension system
- Stainless steel oil collector
- Bakelite handle, cool to touch
- Steel wire pipe to last longer
- Easy access to back rotating shaft, easy to adjust tightness
- Anti slippery rubber foot
- Heating and power indicator
- Splash guard on the bottom plate to prevent food spillage

Model	Plate type	Cooking size	Power	Product (WxDxH)	NW
PG-815	Top grooved + bottom flat	410 x 300 mm 61 x 12 inch	2500 W / 220 ~ 240 V	450 x 370 x 220 mm 18 x 15 x 9 inch	20 kg 44 lbs



PG-2SA



PG-2SC

Panini Grill

- Cast iron plate with ceramic coating to improve efficiency
- Stainless steel structure
- EGO thermostat, durable and robust
- Temperature range 50-320°C
- Hi-limiter ensures safety operation
- Easy access to Reset pole
- Rotating shaft suspension system
- Stainless steel oil collector
- Bakelite handle, cool to touch
- Steel wire pipe to last longer
- Easy access to back rotating shaft, easy to adjust tightness
- Anti slippery rubber foot
- Rock on/off switch with illuminator
- Different plate type available
- Two cooking zones controlled separately



Model	Plate type	Cooking size	Power	Product (WxDxH)	NW
PG-2SA	Top grooved + bottom grooved	475 x 230 mm 19 x 9 inch	2 x 1800 W / 220 ~ 240 V	570 x 305 x 210 mm 22 x 12 x 8 inch	28 kg 62 lbs
PG-2SF	Top flat + bottom flat	475 x 230 mm 19 x 9 inch	2 x 1800 W / 220 ~ 240 V	570 x 305 x 210 mm 22x 12 x 8 inch	28 kg 62 lbs
PG-2SC	Top grooved + bottom flat	475 x 230 mm 19 x 9 inch	2 x 1800 W / 220 ~ 240 V	570 x 305 x 210 mm 22 x 12 x 8 inch	28 kg 62 lbs
PG-2MA	Top grooved + bottom grooved	338 x 220 mm 13 x 9 inch	2 x 2200 W / 220 ~ 240 V	840 x 305 x 210 mm 33 x 12 x 8 inch	33 kg 73 lbs
PG-2MB	Top flat + bottom flat	338 x 220 mm 13 x 9 inch	2 x 2200 W / 220 ~ 240 V	840 x 305 x H10 mm 33 x 12 x 8 inch	33 kg 73 lbs
PG-2MC	Top grooved + bottom flat	338 x 220 mm 13 x 9 inch	2 x 2200 W / 220 ~ 240 V	840 x 305 x 210 mm 33 x 12 x 8 inch	33 kg 73 lbs



FT-818



FT-820

Electric Griddle

- Polished mild steel plate, 10mm in thickness
- Splash guard to prevent food spillage
- Stainless steel structure
- Temperature range 50-300°C
- Large stainless steel oil collector with handle
- Bakelite knob, cool to touch
- Large opening of front grease through
- Stainless steel heating element
- Anti slippery rubber foot
- Heating and power indicator

Model	Plate type	Cooking size	Power	Product (WxDxH)	NW
FT-818	Flat	548 x 350 mm 22 x 14 inch	3000 W / 220 ~ 240 V	550 x 450 x 230 mm 22 x 18 x 9 inch	23 kg 51 lbs
FT-820	Flat	728 x 400 mm 29 x 16 inch	4400 W / 220 ~ 240 V	730 x 500 x 230 mm 29 x 20 x 9 inch	34 kg 75 lbs
FT-822	½ Flat + ½ grooved	728 x 400 mm 29 x 16 inch	4400 W / 220 ~ 240 V	730 x 500 x 230 mm 29 x 20 x 9 inch	34 kg 75 lbs



GR-400

Electric Griddle

- Polished mild steel plate, 12mm in thickness
- Splash guard 2.0mm to prevent food spillage
- Temperature range 50-300°C
- Large stainless steel oil collector with handle
- Bakelite knob, cool to touch
- Large opening of front grease through
- Stainless steel heating element
- Anti slippery rubber foot
- Heating and power indicator

Model	Plate type	Cooking size	Power	Product (WxDxH)	NW
FT-250	Flat	256 x 330 mm 10 x 13 inch	1500 W / 220 ~ 240 V	260 x 420 x 270 mm 10 x 17 x 11 inch	16.5 kg 26 lbs
GR-400	Flat	400 x 396 mm 16 x 16 inch	3000 W / 220 ~ 240 V	400 x 500 x 270 mm 16 x 20 x 11 inch	27.5 kg 60 lbs
GR-550	Flat	546 x 348 mm 22 x 14 inch	3000 W / 220 ~ 240 V	550 x 450 x 270 mm 22 x 18 x 11 inch	31 kg 68 lbs
GR-610	Flat	606 x 400 mm 24 x 16 inch	6000 W / 220 ~ 240 V	610 x 500 x 270 mm 24 x 20 x 11 inch	40 kg 88 lbs
GR-760	Flat	756 x 400 mm 30 x 16 inch	9000 W / 380 V, 3N	760 x 500 x 270 mm 30 x 20 x 11 inch	48 kg 106 lbs

Gas Griddle



FT-718



FT-720

- Polished mild steel plate, 10mm in thickness
- Splash guard to prevent food spillage
- Stainless steel structure
- Stainless steel chimney
- Manual controlled valve with sparking electrode
- Large stainless steel oil collector with handle
- Bakelite knob, cool to touch
- Large opening of front grease through
- H shape burner for better distribution of heat
- Anti slippery rubber foot
- Observation hole for flame status

Model	Plate type	Cooking size	Power	Product (WxDxH)	NW
FT-718	Flat	548 x 350 mm 22 x 14 inch	36520 Btu / 10.7 kW	550 x 530 x 550 mm 22 x 21 x 22 inch	30 kg 66 lbs
FT-720	Flat	548 x 400 mm 22 x 16 inch	39932 Btu / 11.7 kW	730 x 580 x 550 mm 29 x 21 x 22 inch	43 kg 95 lbs

Electric Griddle



EG-24

- Polished mild steel plate, 20mm in thickness
- Splash guard 2.0mm to prevent food spillage
- Stainless steel structure
- Temperature range 50-320°C
- Large stainless steel oil collector
- Bakelite knob, cool to touch
- Protecting grid to protect thermostat knob
- Large opening of front grease through
- Stainless steel heating element
- Stainless steel legs
- Heating and power indicator
- Available in 24", 36" and 48"

Model	Plate type	Cooking size	Power	Product (WxDxH)	NW
EG-24	Flat	605 x 490 mm 24 x 19 inch	8 kW / 380 V, 3N	609 x 616 x 406 mm 24 x 24 x 16 inch	72 kg 158 lbs
EG-36	Flat	910 x 490 mm 36 x 19 inch	12 kW / 380 V, 3N	914 x 616 x 406 mm 36 x 24 x 16 inch	105 kg 231 lbs
EG-48	Flat	1212 x 490 mm 48 x 19 inch	16 kW / 380 V, 3N	1216 x 616 x 406 mm 48 x 24 x 16 inch	138 kg 304 lbs



HS-WS



BH-TP



HS-TW

Hotdog Steamer

- Stainless steel structure
- On/off switch for power
- Cast iron heating plate for sausage
- Ceramic heater for heating spikes
- Cylinder size 200*240mm
- 130°C hi limit for electrical safety of components
- Steel wring rack to separate sausages from both sides
- Stainless steel water pan
- Stainless steel spikes
- Anti-slippery rubber foot

Model	Cylinder size	Heating spike	Power	Product (WxDxH)	NW
HS-WS	Dia. 300 x 240 mm Dia. 12 x 9 inch	Nil	450 W / 230V	240 x 300 x 385 mm 9 x 12 x 15 inch	6.3 kg 14 lbs
BH-TP	Nil	3	240 W / 230V	240 x 300 x 360 mm 9 x 12 x 14 inch	2.6 kg 6 lbs
HS-TW	Dia. 200 x 240 mm Dia. 8 x 9 inch	3	700 W / 230V	467 x 300 x 385 mm 18 x 12 x 15 inch	9.2 kg 20 lbs



BW-A3

Hotdog Warmer

- Stainless steel structure
- Top loading design
- Front and back visual glass
- On/off switch for power
- Stainless steel heating elements
- Holding capacity is up to 100 hotdogs+48 buns
- Water reservoir capacity 6.6 Liters
- Bakelite handle for top cover
- Steaming volume can be adjusted by rotating a cover plate
- Anti-slippery rubber foot
- Front drain tap is easily accessible
- Adjustable temperature from 30~80°C
- Grid support in both compartments

Model	Sausage capacity	Bun capacity	Power	Product (WxDxH)	NW
BW-A3	100	48	1000 W / 230 V	475x 375 x 370 mm 19 x 15 x 15 inch	13 kg 29 lbs

Hotdog Grill



RG-05S



RG-05S with cover



RG-07S

- Stainless steel structure
- Stainless steel rollers
- Energy regulator controlled, durable and robust
- On/off switch for rotating of rollers
- Stainless steel heating elements
- Teflon grease stopper on roller ends
- Heavy duty geared-box motor with cooling fan
- Bottom grease collector
- Wiring grid support inside collector pan to keep hotdog warm
- Anti-slippery rubber foot
- Available in 4 different sizes
- Three models have optional cover

Model	Roller	Optional cover	Power	Product (WxDxH)	NW
RG-05S	5	Yes	400 W / 230 V	590 x 225 x 255 mm 23 x 9 x 10 inch	10 kg 22 lbs
RG-07S	7	Yes	560 W / 230 V	590 x 330 x 255 mm 23 x 13 x 10 inch	13 kg 29 lbs
RG-09S	9	Yes	720 W / 230 V	590 x 405 x 255 mm 23 x 15.9 x 10 inch	15 kg 33 lbs
RG-011S	11	Nil	880 W / 230 V	590 x 480 x 255 mm 23 x 18.9 x 10 inch	17 kg 37 lbs

Bun Warmer



DBG-01

- Stainless steel structure
- 32 buns capacity
- 93°C thermostat
- On/off switch for power
- Stainless steel heating elements
- 100mm depth GN1/1 tray
- Water reservoir capacity 6.6 Liters
- 130°C hi limit for electrical safety of components
- Steel wring rack to separate buns from water
- Anti-slippery rubber foot
- Drawer design with sliding channel

Model	Bun capacity	Temperature	Power	Product (WxDxH)	NW
DBG-01	32	30 - 93°C	450 W / 230 V	604 x 549 x 239 mm 24 x 22 x 9 inch	20 kg 44 lbs



WB-F

Waffle Baker

- Cast iron plate with ceramic coating
- Designed to produce two pieces of 3x5 square pattern waffles
- An output of 30 Belgian waffle in one hour
- Stainless steel structure
- Temperature range 50-320°C
- Waffle thickness can be 1" (2.3cm)
- Top plate opens up to 90°
- EGO thermostat
- Stainless steel heating element on both sides
- Cast iron plate to hold heat longer
- A golden waffle can be done in just 2 minutes
- Anti slippery rubber foot
- Wire brush for easy cleaning
- Bakelite handle for frame ,cool to touch

Model	Plate type	Cooking size	Power	Product (WxDxH)	NW
WB-F	Rectangular	165 x 105 mm 7 x 4 inch	2200 W / 220 ~ 240 V	285 x 360 x 220 mm 11 x 14 x 9 inch	16 kg 35 lbs
WB-F2	Rectangular	165 x 105 mm 7 x 4 inch	2 x 2200 W / 220 ~ 240 V	600 x 360 x 220 mm 24 x 14 x 9 inch	30 kg 66 lbs



WB-H

Waffle Baker

- Cast iron plate with ceramic coating
- Designed to produce five pieces of heart shaped pattern waffles
- An output of 30 Belgian waffle in one hour
- Stainless steel structure
- Temperature range 50-320°C
- Waffle thickness can be 1" (2.3cm)
- Top plate opens up to 90°
- EGO thermostat
- Stainless steel heating element on both sides
- Cast iron plate to hold heat longer
- A golden waffle can be done in just 2 minutes
- Anti slippery rubber foot
- Wire brush for easy cleaning
- Bakelite handle for frame ,cool to touch

Model	Plate type	Cooking size	Power	Product (WxDxH)	NW
WB-H	Heart shape	Dia. 210 mm Dia. 8 inch	2200 W / 220 ~ 240V	285 x 360 x 220 mm 11 x 14 x 9 inch	11 kg 24 lbs
WB-H2	Heart shape	Dia. 210 mm Dia. 8 inch	2 x 2200 W / 220 ~ 240V	600 x 360 x 220 mm 24 x 14 x 9 inch	30 kg 66 lbs

Waffle Baker



WB-1



WB-2

- Cast aluminum plate with Teflon coating
- An output of 20 Belgian waffle in one hour
- Stainless steel structure
- Temperature range 50-270°C
- Waffle thickness can be 2.3cm
- 17cm diameter plate
- Stainless steel heating element on both sides
- Rock on/off switch
- Power indicator
- 5-minute mechanical timer with bell
- Anti slippery rubber foot
- Steel grid handle

Model	Plate type	Cooking size	Power	Product (WxDxH)	NW
WB-1	Round	Dia. 270 mm Dia. 11 inch	1000 W / 220 ~ 240 V	250 x 380 x 300 mm 10 x 15 x 12 inch	7 kg 15 lbs
WB-2	Round	Dia. 270 mm Dia. 11 inch	2 x 1000 W / 220 ~ 240 V	500 x 380 x 300 mm 20 x 15 x 12 inch	17 kg 37 lbs



WB-03D

Waffle Baker

- Cast aluminum plate with Teflon coating
- An output of 20 Belgian waffle in one hour
- Stainless steel structure
- Temperature range 124-230°C
- Waffle thickness can be 1.25" (3cm)
- 18cm diameter plate
- Rotating plate for better batter distribution
- Stainless steel heating element on both sides
- Rock on/off switch with illuminator
- PCB control with precise temperature and time setting
- Buzzer would beep after time is up
- Anti slippery rubber foot
- Stainless steel crumb collector
- Bakelite handle, cool to touch

Model	Plate type	Cooking size	Power	Product (WxDxH)	NW
WB-03D	Round	Dia. 180 mm Dia. 7 inch	1000 W / 220 ~ 240V	255 x 440 x 320 mm 10 x 17 x 13 inch	11 kg 24 lbs



WB-S



Waffle Baker

- Cast iron plate with ceramic coating
- Designed to produce two pieces of 4x6 square pattern waffles
- An output of 30 Belgian waffle in one hour
- Stainless steel structure
- Temperature range 50-320°C
- Waffle thickness can be 1" (2.54cm)
- Top plate opens up to 90°
- EGO thermostat
- Stainless steel heating element on both sides
- Hi limiter for safety of electrical components
- Cast iron plate to hold heat longer
- A golden waffle can be done in just 2 minutes
- Anti slippery rubber foot
- Removable stainless steel crumb collector
- Waffle fork for easy handling of the cooked waffles
- Bakelite handle for frame, cool to touch

Model	Plate type	Cooking size	Power	Product (WxDxH)	NW
WB-S	Rectangular	100 x 160 mm 4 x 6 inch	1500 W / 220 ~ 240 V	470 x 320 x 225 mm 19 x 13 x 9 inch	17 kg 37 lbs



WB-04A



WB-04B

Waffle Baker

- Cast aluminum plate with Teflon coating
- Inner plate can be changed with a screw driver
- An output of 20 Belgian waffle in one hour
- Stainless steel structure
- Temperature range 124-230°C
- Waffle thickness can be 1" (2.54cm)
- 18cm diameter plate
- Rotating plate for better batter distribution
- Stainless steel heating element on both sides
- Rock on/off switch with illuminator
- PCB control with precise temperature and time setting
- Buzzer would beep after time is up
- Anti slippery rubber foot
- Stainless steel crumb collector
- Bakelite handle on both sides, cool to touch

Model	Plate type	Cooking size	Power	Product (WxDxH)	NW
WB-04A	Round	Dia 180 mm Dia 3 inch	1400 W / 220 ~ 240 V	255 x 600 x 305 mm 10 x 24 x 12 inch	11 kg 24 lbs
WB-04B	Round	Dia 180 mm Dia 3 inch	1400 W / 220 ~ 240 V	280 x 600 x 300 mm 11 x 24 x 12 inch	9 kg 20 lbs



QT-1



QT-2



QT-1A



Tongs (optional)

Toaster

- Infrared quartz tube for prompt heating
- Temperature can reach maximum within 30 seconds
- Infrared heating efficiency is much better than regular heating
- Mirror polished stainless steel structure
- Selective switch for different heating groups
- Wiring grid protection to protect quartz tube
- 15 minutes mechanical timer with bell
- Insulation on three sides (Top, Left, Right)
- Stainless steel crumb collector with handle
- Cooling down in seconds after switch is turned off
- Anti slippery rubber foot
- Removable stainless steel crumb collector
- Optional tongs

Model	Layer	Timer	Power	Product (WxDxH)	NW
QT-2	Double	15 min.	3000 W / 220 ~ 240 V	440 x 300 x 400 mm 17 x 12 x 16 inch	10.2 kg 22 lbs
QT-1	Single	15 min.	1700 W / 220 ~ 240 V	440 x 300 x 290 mm 17 x 12 x 11 inch	7.8 kg 17 lbs
QT-2A	Double	15 min.	3000 W / 220 ~ 240 V	470 x 280 x 360 mm 19 x 11 x 14 inch	10.2 kg 22 lbs
QT-1A	Single	15 min.	1700 W / 220 ~ 240 V	470 x 280 x 250 mm 19 x 11 x 10 inch	7.8 kg 17 lbs



ES-2200

Electric Salamander

- Durable stainless steel heater
- Infinite switch with continuous function
- 15 minutes timer with bell
- Stainless steel structure
- Rack support on both sides
- Wiring grid to put food on
- Stainless steel crumb collector at the bottom
- Control to be on the right side to keep away from heat zone
- Cool to touch Bakelite handle on the grid
- Anti slippery rubber foot

Model	Timer	Grid	Power	Product (WxDxH)	NW
ES-2000	15 min	445 x 250 mm 18 x 10 inch	2000 W / 220 ~ 240 V	570 x 340 x 260 mm 22 x 13 x 10 inch	17 kg 37 lbs
ES-2200	Nil	417 x 335 mm 16 x 13 inch	2200 W / 220 ~ 240 V	570 x 390 x 390 mm 22 x 15 x 15 inch	18 kg 40 lbs
ES-4000	Nil	638 x 295 mm 25 x 12 inch	4000 W / 220 ~ 240 V	800 x 450 x 470 mm 32 x 18 x 19 inch	28 kg 62 lbs



CT-2



CT-3

Toaster

- Durable alloy heater
- EGO selective switch for different heating group
- Standby function to save energy at 30% power
- Conveyor belt speed can be adjusted to have different browning
- Geared motor with cooling fan for belt drive
- Specially designed cooling system to cool down top
- Steel guiding net for easy toast
- Slotted cool-to-touch handle for crumb tray
- Insulation on three sides(Top, Left, Right)
- Stainless steel crumb collector with handle
- Front and back discharge can fit different locations
- Adjustable plastic leg
- Available in 3 size

Model	Output	Power	Product (WxDxH)	NW
CT-1	150pcs	1340 W / 220 ~ 240 V	288 x 418 x 387 mm 11 x 17 x 15 inch	14 kg 31 lbs
CT-2	300pcs	2240 W / 220 ~ 240 V	368 x 418 x 387 mm 15 x 17 x 15 inch	16 kg 35 lbs
CT-3	450pcs	2640 W / 220 ~ 240 V	468 x 418 x 387 mm 18 x 17 x 15 inch	20.5 kg 45 lbs



6ATS-BC

Slice Toaster

- Durable mica heaters
- Selective switch for 2 slots or 3 slots
- Manual lifting structure
- 5 minutes timer with bell
- Anti-slippery rubber foot
- Crumb collector at the bottom

Model	No. of Slice	Power	Product (WxDxH)	NW	GW
4ATS-BC	4	2.24 kW / 220~240 V	370 x 210 x 225 mm 15 x 8 x 9 inch	5 kg 11 lbs	5.5 kg 12 lbs
6ATS-BC	6	3.24 kW / 220~240 V	460 x 210 x 225 mm 18 x 8 x 9 inch	6.5 kg 14 lbs	7 kg 15 lbs



CW-72

Cup Warmer

- All stainless steel structure
- Stainless steel heating elements
- On/off power switch with illuminator
- Temperature range 30~60°C
- Top storage area with steel rails around to prevent cups falling
- Perfect for warming cups, plates
- Special shape heating element for even heat distribution
- Warming capacity comes total 72 cups
- Two separate storage levels

Model	Capacity	Temperature	Power	Product (WxDxH)	NW
CW-72	72	30 - 60°C	140 W / 220 ~ 240 V	485 x 445 x 610 mm 19 x 18 x 24 inch	11.5 kg 25 lbs



ES-4000L

Electric Salamander

- Durable alloy heater
- Infinite switch with continuous function
- Stainless steel structure
- Lifting suspension system to stay any position you want
- Wiring grid in the bottom to put food on
- Stainless steel crumb collector with handle
- Recessed control in the front panel to prevent heat radiant
- Cool to touch Bakelite handle on the top
- Anti slippery rubber foot

Model	Height distance	Grid	Power	Product (WxDxH)	NW
ES-2800L	140 mm 5.5 inch	440 x 320 mm 17 x 13 inch	2800 W / 220 ~ 240 V	450 x 450 x 500 mm 18 x 18 x 20 inch	39 kg 86 lbs
ES-4000L	140 mm 5.5 inch	590 x 320 mm 23 x 13 inch	4000 W / 220 ~ 240 V	600 x 450 x 500 mm 24 x 18 x 20 inch	49 kg 108 lbs
ES-5600L	140 mm 5.5 inch	790 x 320 mm 31 x 13 inch	5600 W / 220 ~ 240 V	800 x 450 x 500 mm 32 x 18 x 20 inch	63 kg 139 lbs



BM-165T

Bain Marie

- Stainless steel heater at the bottom of the pan to be cleaned easily
- Stainless steel structure
- Thermostat control, durable and robust
- 165/205mm depth GN1/1 stainless steel inner pan
- Can accommodate all GN size food pans up to 10cm depth
- Foods to be served at temperature of 60~63°C
- Drain tap(two models)for easy removal of water
- Hi limit to prevent dry heating
- Anti slippery rubber foot
- Heating and power indicators
- Available in different sizes

Model	Well depth	Tap	Power	Product (WxDxH)	NW
BM-165	165 mm 6.5 inch	Nil	1200 W / 220 ~ 240 V	355 x 555 x 255 mm 14 x 22 x 10 inch	8 kg 18 lbs
BM-165T	165 mm 6.5 inch	Yes	1200 W / 220 ~ 240 V	355 x 555 x 255 mm 14 x 22 x 10 inch	8 kg 18 lbs
BM-205T	205 mm 8 inch	Yes	1200 W / 220 ~ 240 V	355 x 555 x 255 mm 14 x 22 x 10 inch	8.5 kg 19 lbs



BM-4

Bain Marie

- Immersed heater in water to improve heating efficiency
- Stainless steel structure
- Thermostat controlled, durable and robust
- Temperature range is 30-85°C
- Anti slippery rubber foot
- Heating and power indicators
- Available in different sizes

Model	Insert pan size	No. of insert	Power	Product (WxDxH)	NW
BM-2V	GN 1/2, 10 mm GN 1/2, 4 inch	2	1500 W / 220 ~ 240 V	590 x 385 x 230 mm 23 x 15 x 9.1 inch	9.5 kg 21 lbs
BM-3	GN 1/3, 15 mm GN 1/3, 6 inch	3	1500 W / 220 ~ 240 V	605 x 385 x 280 mm 24 x 15 x 11 inch	12 kg 26 lbs
BM-4	GN 1/2, 15 mm GN 1/2, 6 inch	4	1500 W / 220 ~ 240 V	695 x 610 x 280 mm 27 x 24 x 11 inch	18 kg 40 lbs
BM-4V	GN 1/2, 10 mm GN 1/2, 4 inch	4	1500 W / 220 ~ 240 V	700 x 590 x 230 mm 28 x 23 x 9 inch	16 kg 35 lbs
BM-6V	GN 1/2, 15 mm GN 1/2, 6 inch	6	1500 W / 220 ~ 240 V	695 x 635 x 280 mm 27 x 25 x 11 inch	19 kg 42 lbs



BM-6T

Bain Marie

- Stainless steel heater immersed in water to improve efficiency
- Stainless steel structure
- Thermostat control, durable and robust
- Float switch to prevent dry heating
- 150mm depth GN1/1 stainless steel inner pan
- Comes with S/S GN pan cover
- Foods to be served at temperature of 60~63°C
- Drain tap(two models)for easy removal of water
- EGO 85°C thermostat
- Dismantled stand to save shipping volume
- Sliding rails on both sides can be folded
- Stainless steel bottom shelf for easy storage
- Heating and power indicators
- Available in 4 and 6 pans

Model	Well depth	Tap	Power	Product (WxDxH)	NW
BM-4T	150 mm 6 inch	Yes	2000 W / 220 ~ 240 V	1430 x 1182 x 800 mm 56 x 47 x 32 inch	57 kg 125 lbs
BM-6T	150 mm 6 inch	Yes	2000 W / 220 ~ 240 V	2100 x 1182 x 800 mm 83 x 47 x 32 inch	79 kg 174 lbs



BMP-4



BMP-7

Bain Marie

- Mica heater at the well bottom to improve efficiency
- Stainless steel structure
- Thermostat control, durable and robust
- Circuit breaker to protect electrical components
- Wet Bain Marie structure for better heat transfer
- Foods to be served at temperature of 60~63°C
- Cool to touch Bakelite handle on top cover
- Inner well capacity is available in 3.5 and 7.5 liters
- Anti slippery rubber foot
- Power indicator
- Available in different size

Model	Insert pan capacity	No. of insert	Power	Product (WxDxH)	NW
BMP-4	3.5 L	1	150 W / 220 ~ 240 V	210 x 210 x 320 mm 8 x 8 x 13 inch	3.5 kg 8 lbs
BMP-7	6.5 L	1	200 W / 220 ~ 240 V	255 x 280 x 320 mm 10 x 11 x 13 inch	4.5 kg 10 lbs
BMP-4x2	3.5 L	2	300 W / 220 ~ 240 V	415 x 210 x 320 mm 16 x 8 x 13 inch	6.5 kg 14 lbs
BMP-4x3	3.5 L	3	450 W / 220 ~ 240 V	610 x 210 x 320 mm 24 x 8 x 13 inch	8.8 kg 20 lbs
BMP-4x4	3.5 L	4	600 W / 220 ~ 240 V	415 x 415 x 320 mm 16 x 16 x 13 inch	10.7 kg 24 lbs
BMP-7x2	6.5 L	2	400 W / 220 ~ 240 V	505 x 280 x 320 mm 20 x 11 x 13 inch	7.9 kg 17 lbs



FW-1P



FW-1P-5

Hot Counter Warmer

- Stainless steel heating element at the bottom
- Mirror polished stainless steel structure
- Thermostat control, durable and robust
- Circuit breaker to protect electrical components
- Spot light on top for better view of food displayed
- Three sides colored posters to attract customer
- Temperature display on top to monitor inside temperature
- Light switch with green indicator
- Swing door for easy opening
- Cool to touch Bakelite handle on door
- Sloped shelf for better view from customer
- Anti slippery rubber foot
- Heating indicator
- Available in different sizes

Model	Level	Temperature	Power	Product (WxDxH)	NW
FW-1P	3	30 - 85°C	850 W / 220 ~ 240 V	350 x 425 x 500 mm 14 x 17 x 20 inch	16 kg 35 lbs
FW-1P-5	5	30 - 85°C	850 W / 220 ~ 240 V	350 x 425 x 710 mm 14 x 17 x 28 inch	17 kg 37 lbs



HDS-5

Hot Counter Warmer

- Perspex flip door on both sides, pass through structure
- All stainless steel structure with reinforced frame
- Infinite switch controlled, durable and robust
- Digital temperature display to monitor inside temperature
- Top for dry heating, bottom for humidity heating
- Temperature range 30~85°C
- Automatic water refilling system with manual bypass
- Float switch to prevent heating without water
- See-through structure ensures better view of food
- Humidity heating ensures food to be served warmly fresh and tasty
- Heating lamp switch to be controlled separately
- Perforated pans at the bottom
- Drainage pipe at one side for easy removal of waste water
- Easy access to mica heaters at the bottom for maintenance
- Tong holders on one side
- Anti slippery rubber foot
- Heating indicator

Model	Pan qty.	Power	Product (WxDxH)	NW
HDS-3	Top 330 x 460 mm @ 2pcs Bottom 400 x 600 mm @ 1 pc Top 13 x 18 inch @ 2pcs Bottom 16 x 24 inch @ 1 pc	2840 W / 220 ~ 240 V	914 x 690 x 830 mm 36 x 27 x 33 inch	56 kg 123 lbs
HDS-4	Top 330 x 460 mm @ 3pcs Bottom 400 x 600 mm @ 2pcs Top 13 x 18 inch @ 3pcs Bottom 16 x 24 inch @ 2pcs	4080 W / 220 ~ 240 V	1219 x 690 x 830 mm 48 x 27 x 33 inch	75 kg 165 lbs
HDS-5	Top 16 x 24 inch @ 2pcs Bottom 16 x 24 inch @ 3 pcs Top 16 x 24 inch @ 2pcs Bottom 16 x 24 inch @ 3 pcs	4080 W / 220 ~ 240 V	1536 x 690 x 830 mm 61 x 21 x 33 inch	94 kg 207 lbs



FM-26

Hot Display Case

- Toughened glass all sides
- Thermostat controlled, durable and robust
- Temperature display to monitor inside temperature
- Temperature range 30~90°C
- Cool to touch plastic handle
- Water reservoir at the bottom to add humidity when needed
- Extra deep reservoir GN1/9 x 2.5" to last for whole day
- Three levels of shelves inside chamber
- Shelf height can be adjusted
- Rubber seal between door and frame to prevent heat loss
- Vertical fluorescent lamp on both sides for better food display
- Transparent cover on fluorescent lamps
- Filament lamp on top for advertising posters to attract customer
- On/off switch for lamps
- Anti slippery rubber foot
- Heating indicator
- Available in silver or black color

Model	Capacity	Shelf size	Power	Product (WxDxH)	NW
FM-26	110 L	580 x 275 mm / 23 x 11 inch 580 x 298 mm / 23 x 12 inch 580 x 318 mm / 23 x 13 inch	1840 W / 220 ~ 240 V	660 x 437 x 655 mm 26 x 17 x 26 inch	35 kg 77 lbs
FM-36	150 L	820 x 315 mm / 32 x 12 inch 820 x 340 mm / 32 x 13 inch 820 x 360 mm / 32 x 14 inch	1840 W / 220 ~ 240 V	900 x 480 x 590 mm 35 x 19 x 23 inch	50 kg 110 lbs
FM-48	370 L	1120 x 315 mm / 44 x 12 inch 1120 x 340 mm / 44 x 13 inch 1120 x 360 mm / 44 x 14 inch	2200 W / 220 ~ 240 V	1200 x 480 x 810 mm 47 x 19 x 32 inch	72 kg 158 lbs



FM-36N

Hot Display Case

- Toughened glass all sides
- Thermostat controlled, durable and robust
- Temperature display to monitor inside temperature
- Temperature range 30~90°C
- Cool to touch plastic handle
- Water reservoir at the bottom to add humidity when needed
- Extra deep reservoir GN1/9 x 2.5" to last for whole day
- Three levels of shelves inside chamber
- Shelf height can be adjusted
- Rubber seal between door and frame to prevent heat loss
- Vertical fluorescent lamp on both sides for better food display
- Transparent cover on fluorescent lamps
- Filament lamp on top for advertising posters to attract customer
- On/off switch for lamps
- Anti slippery rubber foot
- Heating indicator
- Attractive two-tone colour

Model	Capacity	Shelf size	Power	Product (WxDxH)	NW
FM-26N	110 L	580 x 275 mm / 23 x 11 inch 580 x 298 mm / 23 x 12 inch 580 x 318 mm / 23 x 13 inch	1800 W / 220 ~ 240 V	660 x 437 x 655 mm 26 x 17 x 26 inch	37 kg 81 lbs
FM-36N	150 L	820 x 315 mm / 32 x 12 inch 820 x 340 mm / 32 x 13 inch 820 x 360 mm / 32 x 14 inch	1840 W / 220 ~ 240 V	900 x 480 x 590 mm 35 x 19 x 23 inch	50 kg 110 lbs
FM-48N	370 L	1120 x 315 mm / 44 x 12 inch 1120 x 340 mm / 44 x 13 inch 1120 x 360 mm / 44 x 14 inch	2200 W / 220 ~ 240 V	1200 x 480 x 810 mm 47 x 19 x 32 inch	72 kg 158 lbs



FW-260



FW-395

Hot Display Case

- Transparent Perspex at all sides
- Stainless steel bottom
- Thermostat control, durable and robust
- Hi limiter to protect electrical components
- Cool to touch plastic handle
- Water reservoir at the bottom to add humidity when needed
- Power switch with green indicator
- Anti slippery rubber foot
- Heating indicator
- Available in single and double levels

Model	Level	Temperature	Power	Product (WxDxH)	NW
FW-260	1	30 - 85°C	250 W / 220 ~ 240 V	500 x 360 x 260 mm 20 x 14 x 10 inch	13 kg 29 lbs
FW-395	2	30 - 85°C	250 W / 220 ~ 240 V	500 x 360 x 395 mm 20 x 14 x 16 inch	14 kg 31 lbs



FW-300



FW-500

Hot Display Case

- Toughened glass sides and door, curved glass in front
- Stainless steel bottom
- Thermostat control, durable and robust
- Hi limiter to protect electrical components
- Cool to touch plastic handle
- Water reservoir at the bottom to add humidity when needed
- Extra deep reservoir GN1/9 x 2.5" to last for whole day
- Inside chamber to be GN1/1 size
- Rubber seal between front and side glass to prevent heat loss
- Anti slippery rubber foot
- Heating indicator
- Available in single and double levels

Model	Level	Temperature	Power	Product (WxDxH)	NW
FW-300	1	30 - 85°C	300 W / 220 ~ 240 V	560 x 395 x 310 mm 22 x 16 x 12 inch	13 kg 29 lbs
FW-500	2	30 - 85°C	500 W / 220 ~ 240 V	560 x 395 x 430 mm 22 x 16 x 17 inch	19 kg 42 lbs



FW-580

Hot Display Case

- Toughened glass front and back
- All stainless steel structure
- Thermostat controlled, durable and robust
- Temperature display to monitor inside temperature
- Temperature range 30~90°C
- Crumb tray at the bottom
- Shelf height can be adjusted
- Sliding door in the front
- On/off switch for lamps
- Anti slippery rubber foot
- Heating indicator

Model	Shelf	Shelf size	Power	Product (WxDxH)	NW
FW-580	4	569 x 300 mm 22 x 12 inch	1000 W / 220 ~ 240 V	640 x 360 x 530 mm 25 x 14 x 21 inch	21 kg 46 lbs
FW-805	5	794 x 300 mm 31 x 12 inch	1500 W / 220 ~ 240 V	865 x 360 x 625 mm 34 x 14 x 25 inch	35 kg 77 lbs



BC0521



BC1121



BC2221

Banquet Cart

- Stainless steel structure
- Good insulation to improve holding efficiency
- 110°C EGO thermostat controlled, durable and robust
- Temperature display on top to read holding temperature
- Water-proof on/off switch
- Double durable stainless steel round heating element
- Forced air circulation with special baffle plate
- Stainless steel lock
- Four swivel heavy duty 6" castors with brake
- Bumpers all around to provide better protection while transportation
- Recessed hand-grasping handle on both sides
- Rubber seal on the doors
- Bottom water tray to keep food humidity when needed
- GN2/1 wiring grid
- Available in 3 different sizes

Model	Capacity	Temperature	Power	Product (WxDxH)	NW
BC1121	22 x GN 1/1	30 - 110°C	2570 W / 230V	780 x 960 x 1755 mm 31 x 38 x 69 inch	182 kg 400 lbs
BC2221	44 x GN 1/1	30 - 110°C	2570 W / 230V	1540 x 960 x 1755 mm 61 x 38 x 69 inch	318 kg 700 lbs
BC0521	10 x GN 1/1	30 - 110°C	2570 W / 230V	780 x 960 x 1355 mm 31 x 38 x 53 inch	145 kg 319 lbs



HC-1M

Hot Cupboard

- All stainless steel structure
- Thermostat controlled, durable and robust
- On/off power switch with illuminator
- Temperature range 30~85°C
- Adjustable plate holder
- Heavy duty door hinge
- Special shape heating element for even heat distribution
- Cool-to-touch Bakelite handle
- Available in 3 different sizes

Model	Capacity	Plate size	Power	Product (WxDxH)	NW
HC-1M	30	Max dia 320 mm Max dia 12 inch	400 W / 220 ~ 240 V	400 x 405 x 545 mm 16 x 16 x 22 inch	24 kg 53 lbs
HC-1	60	Max dia 320 mm Max dia 12 inch	750 W / 220 ~ 240 V	450 x 450 x 850 mm 18 x 18 x 34 inch	33 kg 73 lbs
HC-2	120	Max dia 320 mm Max dia 12 inch	1200 W / 220 ~ 240 V	750 x 450 x 850 mm 30 x 18 x 34 inch	49 kg 108 lbs



PL-3

Plate Warmer

- All stainless steel structure
- On/off power switch
- Temperature range 30~85°C
- Adjustable plate guiding rail to suite different sizes of plates
- Double walled construction reduces heat loss
- Stainless steel heating element
- Drop-in design
- Adjustable spring tension for loading different quantity

Model	Capacity	Plate size	Power	Product (WxDxH)	NW
PL-3	40	Max dia 300 mm Max dia 12 inch	400 W / 220 ~ 240 V	450 x 485 x 770 mm 18 x 19 x 30 inch	19 kg 42 lbs



PL-1



PL-2

Plate Warmer

- All stainless steel structure
- Thermostat controlled, durable and robust
- On/off power switch
- Temperature range 30~85°C
- Adjustable plate guiding rail to suite different sizes of plate
- Double walled construction reduces heat loss
- Stainless steel heating element
- Cool-to-touch Bakelite handle
- Adjustable spring tension for loading different quantity
- Four swivel castors with brake
- Optional black cover

Model	Capacity	Plate size	Power	Product (WxDxH)	NW
PL-1	40	Max dia 300 mm Max dia 12 inch	400 W / 220 ~ 240 V	450 x 485 x 770 mm 18 x 19 x 30 inch	31 kg 68 lbs
PL-2	2 x 40	Max dia 300 mm Max dia 12 inch	800 W / 220 ~ 240 V	450 x 910 x 770 mm 18 x 36 x 30 inch	48 kg 106 lbs



PL-1C



PL-2C

Plate Warmer

- All stainless steel structure
- Thermostat controlled, durable and robust
- On/off power switch
- Temperature range 30~85°C
- Adjustable plate guiding rail to suite different sizes of plates
- Convection design to reduce pre-heating time
- Stainless steel heating element
- Cool-to-touch Bakelite handle
- Adjustable spring tension for loading different quantity
- Four swivel castors with brake
- Optional black cover

Model	Capacity	Plate size	Power	Product (WxDxH)	NW
PL-1C	40	Max dia 300 mm Max dia 12 inch	1000 W / 220 ~ 240 V	435 x 520 x 1025 mm 17 x 21 x 40 inch	28 kg 62 lbs
PL-2C	2 x 40	Max dia 300 mm Max dia 12 inch	2000 W / 220 ~ 240 V	435 x 815 x 1025 mm 17 x 32 x 40 inch	43.5 kg 96 lbs



WL-02

Drawer Warmer

- Stainless steel structure
- Stainless steel heating elements
- Separate heater and control for each drawer
- Moisture control slides
- Analog thermometer
- GN1/1, 6" depth pan
- Steel foot

Model	Power	Product (WxDxH)	NW	GW
WL-02	1 kW / 230 V	740 x 590 x 630 mm 29 x 23 x 25 inch	47 kg 103 lbs	55 kg 121 lbs
WL-03	1.5 kW / 230 V	740 x 590 x 885 mm 29 x 23 x 35 inch	70 kg 154 lbs	84 kg 185 lbs



HC-14

Pass Through Mobile Holding Cabinet

- Stainless steel structure, four doors design
- Stainless steel heating elements
- Two blowers on the top for better hot air circulation
- Digital thermostat
- Self-locking latch
- Water reservoir on top to add humidity

Model	Power	Product (WxDxH)	NW	GW
HC-14	2 kW / 220~240 V	636 x 786 x 2000 mm 25 x 31 x 7 inch	120 kg 264 lbs	150 kg 330 lbs



CM-1



CM-1R



CM-2

Electric Crepe Maker

- All stainless steel structure
- Thermostat controlled, durable and robust
- Cast iron plate with Teflon coating
- Temperature range 30~300°C
- Special shape heating element for even heat distribution
- Two models come with warmer drawer
- Ø 400mm plate
- Anti-slippery rubber foot
- Power indicator
- Wooden crepe spreader
- Available in 3 different sizes

Model	Baking plate	Temperature	Power	Product (WxDxH)	NW
CM-1	Dia. 400 mm Dia. 16 inch	30 - 300°C	3000 W / 220 ~ 240 V	450 x 510 x 240 mm 18 x 20 x 9 inch	21.5 kg 47 lbs
CM-2	Dia. 400 mm Dia. 16 inch	30 - 300°C	6000 W / 220 ~ 240 V	870 x 510 x 240 mm 34 x 20 x 9 inch	40 kg 88 lbs
CM-1R	Dia. 400 mm Dia. 16 inch	30 - 300°C	3000 W / 220 ~ 240 V	Dia. 400 x H200 mm Dia. 16 x H8 inch	20 kg 44 lbs

Gas Crepe Maker



CM-1G

- All stainless steel structure
- Manual gas valve with standby pilot and electrode sparker
- Star burner for better heat distribution
- Large diameter 8-spike burner provide even and constant heating
- Cast iron plate with Teflon coating
- Flame can be adjusted
- Ø 400mm plate
- Anti-slippery rubber foot
- Wooden crepe spreader
- Available in 2 different sizes

Model	Baking plate	Power	Product (WxDxH)	NW
CM-1G	Dia. 400 mm Dia. 16 inch	17000 Btu / 5 kW	450 x 510 x 320 mm 18 x 20 x 13 inch	26 kg 57 lbs
CM-2G	Dia. 400 mm Dia. 16 inch	34000 Btu / 10 kW	870 x 510 x 320 mm 34 x 20 x 13 inch	42 kg 92 lbs



PO-4



PO-4-2

Pizza Oven

- Structure with high temperature black painting
- 500°C EGO thermostat controlled, durable and robust
- 600°C temperature display
- Durable Alloy heating element on top and bottom
- On/off switch for illuminator
- Aluminum painting panel to resist high temperature
- Power indicator
- Visual glass on the door
- Cool to touch Bakelite handle
- Hearthstone inside to make sure temperature is distributed more evenly
- Available in 4 different sizes

Model	Chamber (WxDxH)	Capacity	Temperature	Power	Product (WxDxH)	NW
PO-6-2	610 x 910 x 140 mm 24 x 36 x 6 inch	6 + 6	30 - 500°C	14.4 kW / 380 V	890 x 1125 x 750 mm 35 x 44 x 30 inch	154 kg 339 lbs
PO-6	610 x 910 x 140 mm 24 x 36 x 6 inch	6	30 - 500°C	7.2 kW / 380 V	890 x 1125 x 430 mm 35 x 44 x 17 inch	108 kg 238 lbs
PO-4-2	610 x 610 x 140mm 24 x 24 x 6 inch	4 + 4	30 - 500°C	8.4 kW / 380 V	910 x 820 x 750 mm 36 x 32 x 30 inch	118 kg 260 lbs
PO-4	610 x 610 x 140mm 24 x 24 x 6 inch	4	30 - 500°C	4.2 kW / 380 V	910 x 820 x 430 mm 36 x 32 x 30 inch	68 kg 150 lbs



P18S

Pizza Oven

- Stainless steel structure
- High heat aluminized steel baking chamber
- 360°C EGO thermostat controlled, durable and robust
- Durable stainless steel heating element on top and bottom
- 15-minute timer as a reminder
- Stainless steel handle
- Hearthstone inside to make sure temperature is even
- Stainless steel adjustable legs
- Available in 2 different sizes

Model	Chamber (WxDxH)	Compartment	Temperature	Power	Product	NW
P18S	489 x 476 x 241 mm 19.3 x 18.7 x 10 inch	2	30 - 360°C	2850 W / 230 V	584 x 635 x 530 mm 23 x 25 x 21 inch	55 kg 121 lbs
P22S	565 x 552 x 241 mm 22.2 x 22 x 10 inch	2	30 - 360°C	3600 W / 230 V	660 x 711 x 530 mm 26 x 28 x 21 inch	79 kg 174 lbs



EP-1ST

Counter top pizza oven

- Stainless steel structure
- Comes with ceramic hearth in the cavity
- 12cm deck height
- Compact size for small kitchens
- Temperature range from 280°F- 680°F
- 60 minutes timer with bell
- Gravity door design
- Rubber foot
- Bakelite handle

Model	Cavity size	Stone size	Power	Voltage	Product (WxDxH)	NW
EP-1ST	410 x 420 x 120 mm 16 x 17 x 5 inch	400 x 400 mm 16 x 16 inch	2000 W	240V / 60Hz	560 x 475 x 266 mm 22 x 19 x 11 inch	17 kg 37 lbs
EP-2ST	410 x 420 x 120 mm 16 x 17 x 5 inch	400 x 400 mm 16 x 16 inch	3000 W	240V / 60Hz	560 x 475 x 426 mm 22 x 19 x 17 inch	33 kg 73 lbs



DBS-01

Pizza Oven

- Stainless steel structure
- Stainless steel heating elements
- Top & bottom heating elements
- 15 minutes timer with bell
- Anti-slippery rubber foot
- Crumb collector at the bottom

Model	Power	Product (WxDxH)	NW	GW
DBS-01	1.35 kW / 220~240 V	460 x 380 x 170 mm 18 x 15 x 7 inch	7 kg 15 lbs	8 kg 18 lbs



CP-12

Conveyor Pizza Oven

- Stainless steel structure
- Stainless steel conveyor belt
- Top and bottom heating is controlled separately
- Durable stainless steel heating element on top and bottom
- Cooling fan in the front for cooling down the electrical components
- Conveyor speed can be adjusted
- Locking plate on both ends to be adjusted easily
- Crumb tray on both ends for easy cleaning
- Stainless steel adjustable legs
- Good for pizza, bread, meat
- Available in 2 different sizes

Model	Chamber	Pizza size	Temperature	Power	Product (WxDxH)	NW
CP-12	560 x 385 mm 22 x 15 inch	Dia 300 mm Dia 12 inch	30 - 300°C	6.7kW / 230V	1380 x 555 x 420 mm 54 x 22 x 17 inch	47 kg 103 lbs
CP-18	800 x 540 mm 32 x 21 inch	Dia 460 mm Dia 18 inch	30 - 300°C	10.3kW / 380V	1940 x 740 x 1130 mm 76.4 x 29 x 44 inch	86 kg 189 lbs



CP-12SA

Conveyor Pizza Oven

- Stainless steel structure
- Stainless steel heating elements
- Digital control for time and temperature
- Conveyor speed can be adjusted
- Top and bottom heating elements can be adjusted separately
- Stainless steel legs

Model	Power	Belt Dimension	Product (WxDxH)	NW	GW
CP-12SA	6.7kW / 230V	560 x 385 mm 22 x 15 inch	1380 x 555 x 420 mm 54 x 22 x 17 inch	46 kg 101 lbs	62 kg 136 lbs
CP-18SA	10.3kW / 380V	800 x 540 mm 31 x 21 inch	1940 x 740 x 1130 mm 76.4 x 29 x 44 inch	116 kg 255 lbs	128kg 282 lbs



HP-1800



HP-3600

Electric Hob

- Stainless steel structure
- Energy regulator to set power output as you want
- EGO Infrared hotplate
- Ceramic glass on top
- Glass size 275x275mm
- Heating size Ø 200mm
- No need for pre-heating
- Glow up time is reduced to 6~10 seconds
- Anti-slippery rubber foot

Model	Glass size	Heating zone	Power	Product (WxDxH)	NW
HP-1800	275 x 275 mm 11 x 11 inch	Dia. 200 mm Dia. 8 inch	1800 W / 230 V	350 x 420 x 110 mm 14 x 17 x 4 inch	4.8 kg 11 lbs
HP-3600	500 x 275 mm 20 x 11 inch	Dia. 200 mm Dia. 8 inch	3600 W / 230 V	666 x 420 x 110 mm 26 x 17 x 4 inch	8 kg 18 lbs



TC-1



TC-2

Electrical Buffet Warmer

- Stainless steel structure
- Glass heater underneath
- EGO thermostat adjustable between 30~85°C
- Glass size 526x324mm, heating power at 250W
- Anti-slippery rubber foot
- Optional with handle
- Available in two sizes

Model	Glass size	Heating zone	Power	Product (WxDxH)	NW
TC-1	526 x 324 mm 21 x 13 inch	1	250 W / 230 V	540 x 380 x 85 mm 21 x 15 x 34 inch	5 kg 11 lbs
TC-2	526 x 324 mm 21 x 13 inch	2	500 W / 230 V	680 x 580 x 85 mm 27 x 23 x 34 inch	10 kg 22 lbs



TC-2F

Electric Buffet Warmer

- Stainless steel structure
- Twin infrared Philip lamps on top
- Glass heater underneath
- EGO thermostat adjustable between 30~85°C
- Glass size 526x324mm, heating power at 250W
- On/off switch for heating lamp
- Protective cover
- Anti-slippery rubber foot

Model	Glass size	Lamp	Power	Product (WxDxH)	NW
TC-2F	526 x 324 mm 21 x 13 inch	150 W	1000 W / 230 V	730 x 580 x 550 mm 29 x 23 x 22 inch	14 kg 31 lbs



CS-310

Electric Food Warmer

- Stainless steel structure
- Stainless steel sheathed heating elements on top
- Heating elements for even heat distribution compared with lamps
- Mirror polished radiant plate against heater to improve efficiency
- Easy access from 3 sides for food
- Can be used to keep French fries or any food warm
- Separate on/off switches for lamp and heater
- Raised base to keep heat away from table base
- 2.5" depth GN1/1 food pan at the bottom
- Optional wiring grid for drainage of Fries grease
- Anti-slippery rubber foot



Model	Depth of pan	Lamp	Power	Product (WxDxH)	NW
CS-310	60mm 2.5 inch	40 W	940 W / 230 V	330 x 560 x 500 mm 13 x 22 x 20 inch	7 kg 15 lbs



FFB-10

Electrical French Fries Bagging Station

- Stainless steel structure
- Infrared ceramic heaters on top
- Heating bulbs on top
- Mirror polished radiant plate against heater to improve efficiency
- Can be used to keep French fries or any food warm
- Dumping pan partition to separate different food
- Dumping pan and wiring rack can be interchanged
- Cabinet underneath for storage of stuff
- Perforated pan for drainage of Fries grease
- Stainless steel adjustable legs
- Front stainless steel box and GN pans

Model	Pan heater	Lamp	Power	Product (WxDxH)	NW
FFB-10	60 W	40 W	1100 W / 230 V	1010 x 720 x 1500 mm 40 x 28 x 59 inch	85 kg 187 lbs



WS-02

Burger Station

- Stainless steel structure
- Four stainless steel cup dispenser
- Beverage machines can be installed on top
- Underneath cabinet for storage of stuff
- Ice storage space in the right part
- Heated display counter can be placed on top

Model	Capacity	Pre-set temp	Power	Product (WxDxH)	NW
WS-02	NA	NA	NA	1500 x 760 x 800 mm 59 x 30 x 32 inch	69 kg 152 lbs



EM-809V

Electric Marinator

- Stainless steel structure
- Stainless steel tank with leak proof gasket
- Vacuum pump to marinate meat much faster
- 4 swivel castors for mobility
- Timer control inside
- Buzzer alarms when marinating cycle is finished
- Vacuum meter to monitor inside
- On/off switch to control vacuum pump
- Two plastic containers (one perforated pan)
- Deeper flavor profile can be infused inside proteins
- Marinate on demand to avoid waste

Model	Capacity/cycle	Timing	Power	Product (WxDxH)	NW
EM-809V	36 kg 79 lbs	10 Min	250 W / 230 V	950 x 500 x 940 mm 37 x 20 x 37 inch	78 kg 172 lbs



EM-900

Electric Marinator

- Stainless steel structure
- Stainless steel tank with leak proof gasket
- 4 swivel castors for mobility
- Timer control inside
- Buzzer alarms when marinating cycle is finished
- Two plastic containers (one perforated pan)
- Deeper flavor profile can be infused inside proteins
- Marinate on demand to avoid waste

Model	Capacity/cycle	Timing	Power	Product (WxDxH)	NW
EM-900	36 kg 79 lbs	10 Min	250 W / 230 V	950 x 500 x 940 mm 37 x 20 x 37 inch	62 kg 136 lbs



RG-2

Gas Kebab machine

- High efficiency infrared burners
- Flame failure safety control valve
- Four burners to be controlled separately
- Gear box motor to be rotated
- Large oil collector
- Distance can be adjusted to have different temperatures
- Anti-slippery rubber foot
- V shape cold zone to prevent food debris scorching

Model	Power	Voltage	Product (WxDxH)	NW	GW
RG-2	16 kW	230 ~ 240 V / 120V	534 x 607 x 950 mm 21 x 24 x 37 inch	31 kg 48 lbs	48 kg 106 lbs



PE-2

Electric Kebab Machine

- High efficiency heating elements
- EGO energy regulator
- Four switches to be controlled separately
- Gear box motor to be rotated
- Large oil collector
- Distance can be adjusted to have different temperatures
- Anti-slippery rubber foot

Model	Power	Product (WxDxH)	NW	GW
PE-2	9.9 kW / 380 V	534 x 607 x 950 mm 21 x 24 x 37 inch	31 kg 48 lbs	48 kg 106 lbs



ER-266X

Electric Rotisserie

- Thermostat control up to 300°C
- On/off switch for chamber lights
- On/off switch for rotating motor
- Heavy duty 80W motor for rotation
- Front and back toughened glass
- Rubber seal for air tightness to keep heat inside chamber
- Double handles on glass door
- Oil collector at the bottom
- Four baskets to put chicken pieces inside
- Optional spit to choose
- Swivel castors for easy movement

Model	Capacity	Temperature	Power	Product (WxDxH)	NW
ER-266X	12 birds	30 - 300°C	4500 W / 230 V	810 x 630 x 610 mm 32 x 25 x 24 inch	66 kg 145 lbs
ER-268X	16 birds	30 - 300°C	6000 W / 230 V	1010 x 630 x 800 mm 40 x 25 x 32 inch	90.5 kg 199 lbs



GR-268-1

Gas Rotisserie

- All stainless steel structure
- Digital temperature control up to 300°C
- Gas infrared burner
- Automatic solenoid valve to ensure gas safety
- On/off switch for chamber lights
- On/off switch for rotating motor
- Heavy duty 80W motor for rotation
- Front and back toughened glass
- Rubber seal for air tightness to keep heat inside chamber
- Double handles on glass door
- Oil collector at the bottom
- Four baskets to put chicken pieces inside
- Optional spit to choose
- Swivel castors for easy movement

Model	Capacity	Temperature	Power	Product (WxDxH)	NW
GR-268-1	16 birds	30 - 300°C	32341 Btu / 9.5 kW	1010 x 810 x 800 mm 40 x 32 x 32 inch	91 kg 200 lbs



TBZ-4R

Gas Hotplate

- All stainless steel structure
- Cast iron crown burner
- Cast iron grate on top
- Standby pilot for instant start of main burner
- Gas control valve with solenoid inside for safety operation
- Cool to touch fiberglass Nylon knobs
- Easy conversion between different types of gases
- Stainless steel legs

Model	Burner	Power	Product (WxDxH)	NW
TBZ-4R	4	100,000 Btu / 29.3 kW	609 x 731 x 320 mm 24 x 29 x 13 inch	44 kg 97 lbs



TFT-21R

Gas Griddle

- All stainless steel structure
- Cast iron flat burner
- 16mm thickness griddle plate(590×434mm)
- Two separate cooking zones
- Standby pilot for instant start of main burner
- Gas control valve with solenoid inside for safety operation
- Cool to touch fiberglass Nylon knobs
- Stainless steel splash guards at 3 sides
- Easy conversion between different types of gases
- Piezo ignition for easy start of flame
- Observation holes for the main flame status
- Stainless steel legs

Model	Burner	Cooking zone	Power	Product (WxDxH)	NW
TFT-21R	2	590 x 434 mm 23 x 17 inch	27400 Btu / 8kW	600 x 612 x 470 mm 24 x 24 x 19 inch	50 kg 110 lbs



TZL-2R

Gas Fryer

- All stainless steel structure
- U shape burner
- 8 liters capacity per tank
- Two separate cooking zones
- Standby pilot for instant start of main burner
- Gas control valve with solenoid inside for safety operation
- Cool to touch fiberglass Nylon knobs
- Drain cock for oil tank
- Easy conversion between different types of gases
- Piezo ignition for easy start of flame
- Observation holes for the main flame status
- Stainless steel legs

Model	Tank	Capacity / tank	Power	Product (WxDxH)	NW
TZL-2R	2	8 L	38400 Btu / 11.2 kW	600 x 612 x 470 mm 24 x 24 x 19 inch	32 kg 70 lbs



TSK-2R

Gas Lava Rock Grill

- All stainless steel structure
- 4 cast iron flat burner
- Lava rock to hold heat and give off more evenly
- Lava rock to give food a taste of charcoal
- Two separate cooking zones
- Standby pilot for instant start of main burner
- Gas control valve with solenoid inside for safety operation
- Cool to touch fiberglass Nylon knobs
- Cast iron cooking grate on top to give burning marks
- Oil to be collected through channels in the front
- Easy conversion between different types of gases
- Piezo ignition for easy start of flame
- Observation holes for the main flame status
- Stainless steel legs

Model	Controls	Cooking zone	Power	Product (WxDxH)	NW
TSK-2R	2	560 x 324 mm 22 x 13 inch	54800 Btu / 16 kW	600 x 612 x 470 mm 24 x 24 x 19 inch	60 kg 132 lbs



TFT-21

Electric Griddle

- All stainless steel structure
- Stainless steel heater with insulation outside
- 16mm thickness griddle plate(536x330mm)
- Thermostat control from 30~300°C
- Power and heating indicators
- Cool to touch fiberglass Nylon knobs
- Stainless steel splash guards at 3 sides
- Two separate cooking zones
- Oil to be collected through channels in the front
- Stainless steel legs

Model	Cooking zone	Temperature	Power	Product (WxDxH)	NW
TFT-21	536 x 330 mm 21 x 13 inch	30 - 300°C	5000 W / 230 V	600 x 600 x 350 mm 24 x 24 x 14 inch	43 kg 95 lbs



TTC-4

Electric Bain Marie

- All stainless steel structure
- Stainless steel heater immersed in water for better efficiency
- 15 liters capacity
- Thermostat control from 30~100°C
- Power and heating indicators
- Drain cock for each tank
- Cool to touch fiberglass Nylon knobs
- Different sizes of insert pans
- Stainless steel legs

Model	Capacity	Temperature	Power	Product (WxDxH)	NW
TTC-4	15 L	30 - 100°C	1.5 kW / 230 V	700 x 600 x 350mm 28 x 24 x 14 inch	35 kg 77 lbs



TZL-2

Electric fryer

- All stainless steel structure
- Stainless steel heater with insulation outside
- 8 liters capacity per tank
- Thermostat control from 30~190°C
- Power and heating indicators
- 230°C hi limit for safety of oil
- Cool to touch fiberglass Nylon knobs
- Bakelite handle of frying basket
- Two separate cooking zones
- Micro switch
- Stainless steel legs

Model	Capacity	Temperature	Power	Product (WxDxH)	NW
TZL-2	8 L + 8 L	30 - 190°C	3.25 kW x 2 / 230V	600 x 600 x 430 mm 24 x 24 x 17 inch	22 kg 48 lbs



TZM-3

Electric Noodle Boiler

- All stainless steel structure
- Stainless steel heater immersed in water for better efficiency
- 6 liters capacity per tank
- Three separate tanks
- Thermostat control from 30~100°C
- Power and heating indicators
- Drain cock for each tank
- Cool to touch fiberglass Nylon knobs
- Two baskets for each tank
- Stainless steel legs

Model	Capacity	Temperature	Power	Product (WxDxH)	NW
TZM-3	6 L + 6 L + 6 L	30 - 100°C	2 kW x 3 / 230 V	600 x 600 x 350 mm 24 x 24 x 14 inch	25 kg 55 lbs

Gas Salamander



RG-16

- Cast iron infrared burner
- Gas valve with automatic electrode
- Adjustable wiring grid to achieve different temperature
- Stainless steel structure
- Wiring grid to put food on
- Stainless steel crumb collector at the bottom
- Four burners and six burners are available
- Anti slippery rubber foot

Model	Controls	Grid	Power	Product (WxDxH)	NW
RG-14	4	411 x 366 mm 16 x 14 inch	23891 Btu / 7 kW	620 x 440 x 610 mm 24 x 17 x 24 inch	32 kg 70 lbs
RG-16	6	411 x 366 mm 16 x 14 inch	35154 Btu / 10.3 kW	880 x 440 x 620 mm 35 x 17 x 24 inch	47 kg 103 lbs



GS24L

Gas Broiler with Griddle top

- Stainless steel front, galvanized sides
- Cast iron open burner, each 18,000 BTU/hr
- Flame failure control on each burner
- Welded frame structure for best stability
- Griddle plate(3/4" thickness) with splash guard
- 8.25"high broiler opening with a built-in rack that can slide
- Adjustable heavy duty legs
- Large grease collector
- A pull-out crumb tray with angled handle in the front
- Cabinet with double doors
- Piezo igniter for easy starting of pilot
- Continuous pilot
- Bakelite handle
- 3/4" NPT rear gas connection
- Natural gas or LP gas, easy conversion in field

Model	No. of Burner	Power	Product (WxDxH)	NW
GS24L	3	54,000 Btu / hr	610 x 815 x 965 mm 24 x 32 x 38 inch	70 kg 154 lbs
GS36L	5	90,000 Btu / hr	914 x 815 x 965 mm 36 x 32 x 38 inch	103 kg 227 lbs



6G-TRC-2

Gas fryer

- All Stainless steel structure
- Stainless steel burner
- Stainless steel tank
- Mini SIT 710 control thermostat valve
- EGO hi limiter for safety
- One basket per tank
- Pulse ignition system
- Standby S/S pilot for easy start
- Adjustable heavy duty legs
- Oil drain extension
- Basket support grid
- Available in single tank or double tanks
- Different varieties of products for different purposes
- Easy gas conversion in field
- 3/4" NPT rear gas connection

Model	Tank Capacity	Power	Product (WxDxH)	NW
6G-TRC-1	8 ~ 10 L	5.6 kW	400 x 651 x 475 mm 16 x 26 x 19 inch	25 kg 55 lbs
6G-TRC-2	8 ~ 10 L x 2	5.6 kW + 5.6 kW	600 x 651 x 476 mm 35 x 17 x 19 inch	30 kg 66 lbs



6G-TRM60

Gas noodle boiler

- All Stainless steel structure
- Stainless steel straight burner, each 6kW
- Front water inlet pipe
- Drainage pipe for discharging water
- Battery sparkler for easy ignition
- Water overflow in the front
- Adjustable heavy duty legs
- Durable brass control valve with continuous pilot
- Stainless steel basket
- Easy gas conversion in field
- 3/4" NPT rear gas connection

Model	Tank Capacity	Power	Product (WxDxH)	NW
6G-TRM40	17 L	6 kW	400 x 650 x 540 mm 16 x 26 x 21 inch	30 kg 660 lbs
6G-TRM60	28 L	6 kW x 2	600 x 650 x 540 mm 24 x 26 x 21 inch	40 kg 880 lbs



6G-TRH60

Gas Lava Rock Grill

- All Stainless steel structure
- Stainless steel U shape burner, each 8kw
- Splash guard at three sides
- Cast iron cooking grates
- Cooking grates can be reversed for different food
- Cooking grate height can be adjusted
- Oil collector at the bottom
- Pulse ignition system
- Adjustable heavy duty legs
- Durable brass control valve
- Lava rock to give best taste
- Optional radiant kits available
- Easy gas conversion in field

Model	Stone size	Power	Product (WxDxH)	NW
6G-TRH40	400 x 460 mm 16 x 18 inch	8 kW	400 x 650 x 540 mm 16 x 26 x 21 inch	30 kg 66 lbs
6G-TRH60	600 x 460 mm 24 x 18 inch	8 kW x 2	600 x 650 x 540 mm 24x 26 x 21 inch	45 kg 99 lbs



6G-TRG60

Gas griddle

- All Stainless steel structure
- Gas U shape burner
- Piezo igniter
- Flame failure control system
- Stainless steel heating elements
- Splash guard at three sides
- 14mm thickness griddle plate
- Hard chrome coating surface, easy to clean
- Heat can be retained for better efficiency
- Oil collector at the bottom
- Two separate cooking zone
- Adjustable heavy duty legs

Model	Cooking surface	Power	Product (WxDxH)	NW
6G-TRG40	400 x 455 mm 16 x 18 inch	6 kW	400 x 650 x 540 mm 16 x 26 x 21 inch	97 kg 154 lbs
6G-TRG60	600 x 455 mm 24 x 18 inch	12 kW	600 x 650 x 540 mm 24 x 26 x 21 inch	65 kg 143 lbs



SP-300

Gas Stock Pot

- All stainless steel frame structure
- Manual safety gas valve with electrode sparker
- Crown burner flame delivers 6kw power
- Copper flame spreader
- Cast aluminum burner support to provide perfect gas and air mixture
- Cast iron heavy duty 400x400mm cooking grate with enamel coating
- Conversion kit for different gas types
- Designed for commercial use

Model	Grate size	Power	Product (WxDxH)	NW
SP-300	400 x 400 mm 16 x 16 inch	20478 Btu / 6 kW	400 x 400 x 390 mm 16 x 16 x 15 inch	10 kg 22 lbs



SP-1A

Gas Stock Pot

- Dual ring cast iron burner
- Heavy duty cast iron grate
- Standby pilot for easy start
- Stainless steel adjustable heavy duty legs
- Zinc alloy knob with chrome coating
- Crumb tray at the bottom
- Easy conversion from natural gas to Propane or vice versa
- Stainless steel in the front and sides
- Available in single and double burners

Model	Grate size	Power	Product (WxDxH)	NW
SP-1A	456 x 456 mm 18 x 18 inch	80,000 Btu / 23.4 kW (NG) 50,000 Btu / 14.6 kW (LP)	456 x 530 x 493 mm 18 x 21 x 19 inch	47 kg 103 lbs
SP-2A	456 x 456 mm 18 x 18 inch	80,000 x 2 Btu / 23.4 x 2 kW (NG) 50,000 x 2 Btu / 14.6 x 2 kW (LP)	456 x 1050 x 493 mm 18 x 41 x 19 inch	89 kg 106 lbs